

iW 62TDC

The iW 62 TDC is Tannoy flagship in-wall speaker in the iW series, combining the abilities and per Dual Concentric driver technology, a SuperTweer and an auxiliary bass driver for extended low fr a large format chassis built from UV stabilized ABS, the iW 62 TDC leverages the performance of and adds a second 165 mm (6.50") bass driver for astounding bass response down to 35Hz.


View more images

Solidly built and capable of withstanding continuous 120Watts RMS power handling and short te that power, the iW 6 TDC's high efficiency design (92dB/Watt) means it is capable of exceptional *l* outstanding dynamic range. For fine tuning the speaker performance to the room a front mount adjustment on the HF output energy.

High-end features include the ability to bi-wire or bi-amplify the iW 62 TDC for peak audio perfor pairs of gold plated spring terminals and Tannoy's unique fifth terminal to ground the driver chathe system, which can reduce the potential for hum and improve sound quality. Eight of Tannoy's clamps are used to fit the iW 62 TDC rigidly into the wall cavity, creating a solid and stable platfor

The iW 62 TDC is a genuine full range in-wall loudspeaker with a linear response from 34Hz to 51 renowned sound quality. Ideally suited to larger to larger installations where higher power output TDC offers premium performance for home theatre or multi-room distributed audio systems. Su paintable grille and comprehensive fitting instructions, the iW 62 TDC is Tannoy's flagship iW seri

Read less



_

TANNOY						Search	h	f in		
	Home	News	Products	Events	Where to buy	Support	About L	Js		
	Driv	er Complement			SuperTweeter™: 25r Dual Concentric™: 1 Bass driver: 165mm	65mm (6.50")				
	CRO	SSOVER								
	Frequency				750Hz, 1.8kHz, 16kH	z				
	Туре				Passive					
	OPT	IONAL THP 60 T								
	Max	Maximum SPL (4)								
	Wat	Wattage Tap Selections								
	CON	ISTRUCTION								
	Finish				White - paintable					
	Connectors				Gold plated spring terminals					
	Dimensions (H x W)				Front Baffle: 473.5 x 227mm (18.64 x 8.94") Maximum wall thickness: 25mm (1.00")					
	Cut-out Dimensions (H x W)				Maximum wall thickness: 25mm (1.00") 426.10 x 187.60mm (16.76 x 7.39")					
	Rec. in-wall Mounting Volume				30 litres (1.1 cu.ft.)					
	Mounting Depth				99mm (3.89")					
	Weight (each)				5kg (11lbs)					
	Accessories				Pre-installation ring Back can Back can with 60 Watt transformer					
	pow	er handling capaci	ty as defined in El	A standard RS	5 - 426A. Crest factor 6. (4 Ba	4) Unweighted	pink noise inp	but, measure	d at 1m in an an	ech
					Specifications	Sup	oport			
	Support									
	Tannoy prides itself on high quality workmanship, outstanding sound quality and the longevity of its products. No other loudspeaker as many vintage loudspeakers still delighting their owners to this day. Click on the links below for warranty information, FAQs on set loudspeakers and downloadable manuals. Please take the time to register your new Tannoy loudspeakers so we can keep you up to our products, news and events.									
	Register your product					Dow	vnload Manu	al		
	Please take the time to register your new Tannoy loudspeakers.								n of the produ	ct u
	FAQ					-\W/ar	ranty			
	 Frequently asked Questions on getting the best f loudspeakers. 				from Tannoy	• In		i Tannoy's co	omprehensive	oro
										-

TANNOY						Search	f	in E	You Tube
	Home	News	Products	Events	Where to buy	Support	About Us		
		Contact Us © Copyrigh	About Careers	Imprint & T	erms of Use Priv al SC Ltd. All rights r	acy Policy			
		© Copyrigh							