


sAp-1

Shenzhen shuangmusanlin electronics Co., LTD





Specifications

Output Power:

32Ω 270mW 64Ω 170mW 150Ω 88mW 300Ω 48mW THD+N: 0.001%

SNR: 0.0019

Power consumption:

CAUTION

There are two versions of sAp-1 differed in voltage

AC 110V (100-120V)

AC 220V (200-240V)

RISK OF ELECTRIC SHOCK

Warnin

Preventing hearing damage avoid using headphones/ earphones at high volume. Hearing experts advise against continuous, loud and extended play. If you experience a ringing in your ears, reduce volume or discontinue use.



The lightning lash with arrowhead symbol, with in an equilateral triangle, is intended to alert the user to the presence of uninsulated" dangerous voltage within the product's enclosure that may be of sufficient magnitude to constitute a risk of electric shock to persons.



The exclamation point within an equilateral triangle is intended to alert the user to the presence of important operating and maintenance (servicing) instructions in the literature accompanying the appliance.



Only suitable for area which altitud e under 2000m.



Only for Non tropical climate circumstance usage.

Shenzhen Shuangmusanlin Electronics Co., Ltd. Address:8th Floor B6 Building Jun Feng Industrial Park, Fuyong town, BaoAn District Shenzhen, China Tel: +86-755-27444178

http://www.smsl-audio.com/