

Install Speakers

VLS 30-WH

Passive Column Array Loudspeaker with 30 Drivers and FAST Dispersion Control for Installation Applications (White)

- Passive column array loudspeaker for indoor and outdoor installation applications
- 400 Watts continuous, 1,600 Watts peak power
- 14 vertically arrayed 3.5" low frequency drivers provide high intelligibility speech reproduction
- 16 vertically arrayed 1" high frequency metal dome tweeters for full range sound up to 35 kHz
- FAST (Focussed Asymmetrical Shaping Technology) delivers asymmetric vertical dispersion towards the typical listening plane
- Multiple transformer taps for 70 V and 100 V line systems or 6 Ohm direct input
- Low insertion loss 150 W line transformer with easily accessible tapping switch
- All components weather resistant to IP65 for outdoor use
- Architecturally styled aluminium enclosure with a semi matt white painted finish
- Corrosion resistant stainless steel perforated grille
- Included custom brackets allow quick and accurate installation
- 10-Year Warranty Program*
- Designed and engineered in the U.K.

The VLS 30-WH is an 1600-Watt passive column array loudspeaker ideally suited for challenging acoustic and architecturally sensitive spaces where background/foreground music and speech reinforcement is required. Applications include airports, train stations, conference centers, houses of worship, stadium concourses, museums, theme parks and hotels. The heart of the loudspeaker system is its asymmetrical vertical dispersion, which gently shapes the acoustic coverage towards the lower quadrant of the vertical axis. VLS 30-WH's Focused Asymmetrical Shaping Technology™ (FAST) also facilitates quick and easy installation, with less need for tilting for optimal mounting. VLS 30-WH packages this performance in a slender and narrow profile, aesthetically refined, powder coated aluminum chassis with curved stainless steel grille.



Install Speakers

VLS 30-WH

Passive Column Array Loudspeaker with 30 Drivers and FAST Dispersion Control for Installation Applications (White)



Superb Performance

VLS 30-WH's design comprises 14 vertically arrayed 3.5" low frequency drivers and 16 vertically arrayed 1" high frequency metal dome tweeters for pristine audio reproduction from 90 Hz - 35 kHz (-10 dB), with 126 dB peak SPL (1 m, Lo-Z). The UV and weather resistant aluminium enclosure provides 130° horizontal x +3° / -11° vertical dispersion for targeted coverage. Also certified for water and dust ingress protection to IP65 standard, the VLS 30-WH is an exceptional choice for challenging environments such as indoor swimming pools, saunas, or work areas with unusually high levels of dust or moisture, and outdoor applications.

FAST – Focused Asymmetrical Shaping Technology

Designed with an asymmetrical vertical dispersion pattern, the VLS 30-WH merges enhanced performance with simplified mounting to cover a wide range of installed applications. The vertical dispersion of the VLS 30-WH allows optimal zones to be targeted for even and precise coverage. Additionally, in installations where most conventional column loudspeakers require substantial downward tilt, the VLS 30-WH requires much less – even enabling flush mounting, for significantly improved visual aesthetics.



Low-Z or Transformer Operation

A multi-position EN 54 compliant tamper-resistant rotary switch on the rear panel allows the choice of either the low-Z, or the 70 / 100 V operating modes, with available transformer taps at 150; 75; 37.5; 19; 9.5, and 5 Watts.

Install Speakers

VLS 30-WH

Passive Column Array Loudspeaker with 30 Drivers and FAST Dispersion Control for Installation Applications (White)

Outdoor Applications

A right angled water tight cable gland is supplied with the VLS 30-WH for use in outdoor applications with an input panel cover is secured to the cabinet using the four screws. Simply pass the wiring through the cable gland and make your connections on the provided barrier strip. A second strip is provided for linking additional loudspeakers in either low-Z, or 70 / 100 V distributed systems.



Attractive & Easy to Install

The stylish and durable extruded aluminium enclosure with stainless steel grille features a semi matt white paint finish that fits unobtrusively into even the most architecturally sensitive environments. Input is via a low insertion loss 150 W line transformer with multiple taps for 70 / 100 V line systems. A dedicated flying bracket, wall mount bracket, input panel cover plate, and weather resistant gland are all included for ease of installation. At only 19 kg (41.8 lbs), the VLS 30-WH is significantly lighter and easier to install than many competing products.

Connections


Utilising a pair of internally paralleled barrier strip connectors, the VLS 30-WH can either be connected to a low-Z amplifier, or used within a 70 / 100 V distributed system. The operation mode is easily selectable via a single switch located on the rear of the enclosure.



Install Speakers

VLS 30-WH

Passive Column Array Loudspeaker with 30 Drivers and FAST Dispersion Control for Installation Applications (White)



Build Quality

The architecturally styled corrosion resistant extruded aluminium enclosure is finished in a semi matt white paint and is complemented by a stainless steel perforated grille. All VLS 30-WH mounting hardware is included and over-engineered for the ultimate in safety.

You Are Covered

We always strive to provide the best possible Customer Experience. Our products are made in our own MUSIC Tribe factory using state-of-the-art automation, enhanced production workflows and quality assurance labs with the most sophisticated test equipment available in the world. As a result, we have one of the lowest product failure rates in the industry, and we confidently back it up with a generous Warranty program.




Install Speakers

VLS 30-WH

Passive Column Array Loudspeaker with 30 Drivers and FAST Dispersion Control for Installation Applications (White)

Dimensions



Install Speakers

VLS 30-WH

Passive Column Array Loudspeaker with
30 Drivers and FAST Dispersion Control
for Installation Applications (White)

Technical Specifications

System

Frequency response	120 Hz - 22 kHz \pm 3 dB 90 Hz - 35 kHz -10 dB
Horizontal dispersion (-6 dB)	130° H
Vertical dispersion (-6 dB)	+3° / -11° V (-4° bias)
Power handling (IEC)	400 W average, 800 W continuous, 1600 W peak
Recommended amplifier power	1200 W @ 4 Ω
System sensitivity	94 dB (1 m, Lo Z)
Sensitivity (per EN54-24)	—
Nominal impedance (Lo Z)	6 Ω
Maximum SPL (per EN54-24)	—
Rated maximum SPL	120 dB continuous, 126 dB peak (1 m, Lo Z)
Crossover	Passive, utilizing Focussed Asymmetrical Shaping Technology (FAST)
Crossover point	2.5 kHz
Directivity factor (Q)	15 averaged, 1 kHz to 10 kHz
Directivity index (DI)	11.8 average, 1 kHz to 10 kHz
Components	14 x 3.5" (89 mm) woofers 16 x 1" (25 mm) metal dome tweeters

Transformer taps (via rotary switch) (Rated noise power and impedance)

70 V	150 W / 75 W / 37.5 W / 19 W / 9.5 W / 5 W / OFF & low impedance operation
100 V	150 W / 75 W / 37.5 W / 19 W / 9.5 W / OFF & low impedance operation

Coverage angles

500 Hz	220° H x 41° V
1 kHz	200° H x 21° V
2 kHz	120° H x 17° V
4 kHz	120° H x 20° V

Enclosure

Connectors	Barrier strip
Wiring	Terminal 1+ / 2- (input); 3- / 4+ (link)
Dimensions H x W x D	1461 x 121 x 147 mm (57.5 x 4.8 x 5.8")
Net weight	19 kg (41.8 lbs)
Construction	Aluminium extrusion
Finish	Paint RAL 9003 (white) Custom RAL colours available (additional cost and lead-time)
Grille	Powder coated perforated steel
Flying hardware	Flying bracket, wall mount bracket, input panel cover plate and gland

Notes:

- (1) Average over stated bandwidth. Measured in an IEC baffle in an Anechoic Chamber
- (2) Unweighted pink noise input, measured at 1 metre on axis
- (3) Long term power handling capacity as defined in IEC268-5 test
- (4) The reference point for the reference axis (on-axis) is the centre of the baffle

Install Speakers

VLS 30-WH

Passive Column Array Loudspeaker with
30 Drivers and FAST Dispersion Control
for Installation Applications (White)



Install Speakers

VLS 30-WH

Passive Column Array Loudspeaker with
30 Drivers and FAST Dispersion Control
for Installation Applications (White)



Install Speakers

VLS 30-WH

Passive Column Array Loudspeaker with
30 Drivers and FAST Dispersion Control
for Installation Applications (White)



Install Speakers

VLS 30-WH

Passive Column Array Loudspeaker with
30 Drivers and FAST Dispersion Control
for Installation Applications (White)



For service, support or more information contact the TANNOY location nearest you:

Europe
MUSIC Tribe Brands UK Ltd.
Tel: +44156 273 2290
Email: CARECrea@music-group.com
CAREEnte@music-group.com
CARELife@music-group.com

USA/Canada
MUSIC Tribe Commercial NV Inc.
Tel: +1 702.800 8290
Email: CARECrea@music-group.com
CAREEnte@music-group.com
CARELife@music-group.com

Japan
MUSIC Tribe Services JP K.K.
Tel: +81 3 6231 0453
Email: CARECrea@music-group.com
CAREEnte@music-group.com
CARELife@music-group.com

MUSIC Tribe accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph, or statement contained herein. Technical specifications, appearances and other information are subject to change without notice. All trademarks are the property of their respective owners. MIDAS, KLARK TEKNIK, LAB GRUPPEN, LAKE, TANNNOY, TURBOSOUND, TC ELECTRONIC, TC HELICON, BEHRINGER, BUGERA and COOLAUDIO are trademarks or registered trademarks of MUSIC Group IP Ltd.
© MUSIC Group IP Ltd. 2018 All rights reserved.

TANNOY