**Legendary Dynaudio performance in your outdoor or marine space.** Use them in passive mode or in a 70/100V line system for incredible flexibility.

## **Outdoor series** On-wall



**DYNAUDIO** 

## Outdoor series On-wall

- 2-way systems
- 6" and 8" versions
- Comes in black and white color with UV resistance
- IP65 rated
- 8 ohm / 70V / 100V
- · Swivel wall bracket

Model number / in-ceiling	OW-6	OW-8
		200
Туре	2-way on-wall	2-way on-wall
Drivers	Tweeter: 25mm (1in); mid/bass: 165mm (6½in)	Tweeter: 25mm (1in); mid/bass: 200mm (8in)
Performance frequency response (+/- 3dB)	78Hz – 20kHz	70Hz – 20kHz
Impedance (nominal/minimum)	8Ω /5Ω	8Ω /5Ω
Sensitivity (dB SPL [2.83V/1m])	89dB	89dB
Rated power*	50W	60W
Long term power*	100W	100W
Input selector	8Ω / 70V / 100V	8Ω / 70V / 100V
Dimensions (W x H x D)	180 x 285 x 175 mm (7½ x 11½ x 6¾in)	210 x 340 x 196 mm (8¼ x 13% x 7¾in)
Weight	4.5kg	5.0kg
IP rating	IP65	IP65
Colour	White/black	White/black
Certifications	CE	CE
Environmental	RoHS	RoHS