


# M588

# 小型摄影拾音麦克风

COMPACT VIDEO MICROPHONE



#### **GENERAL INTRODUCTION**

M588 is a compact microphone designed to improve the audio quality of your videos. A directional microphone reduces distracting peripheral sounds and focuses on the audio in front of the camera. With its cardioids polar pattern, it picks up the sound more natural and pure, when recording outside. The windscreen reduces the noise and unwanted sound during recording. This microphone is mainly used in SLR cameras or camcorders, offering high quality sound. It also comes with a camera and shock mount.

#### INSTALLATION

#### Mounting to camera:





Insert microphone body into the captive mount on the shock mount. Ensure the microphone body is centered and well balanced.





Turn the tightening ring above the camera shoe mount counter-clockwise to loosen the camera shoe connection, slide the camera shoe into place on the camera mount. Once the microphone is in place, secure it by tightening the ring clockwise.




Connect one end of the 3.5mm output socket on the rear of the microphone and the other end of 3.5mm output cable to the camera's "microphone in" socket.

#### Mounting to boom pole or microphone stand





Connect the 3/8" thread on the bottom of the camera shoe mount to the 3/8" thread used on your boom pole or microphone stand.



Rotate clockwise until connection is secure. Do not over-tighten.

#### **FEATURE**

- \* Saving-space, modeling lightness;
- \* High sensitivity, wide frequency response;
- \* Strong practicability;
- \* Capture the sound accurately.

#### APPLICATION



#### **SPECIFCATION**

- \* Polar pattern: cardioid
- \* Frequency response: 10hz-20khz
- \* Max SPL: 140dB(@1khz, 1% THD into 1kohm load)
- \* Sensitivity: -33dB
- \* Equivalent noise level: 20dB

Copyright © Ningbo Alctron Electronics Technology CO.,LTD. All rights reserved. Specifications and appearance subject to change without notice.

Ningbo Alctron Electronics Technology CO.,LTD.

No.76 SanCheng Road, XiuFeng Industrial Area,GaoQiao Town, NingBo, China.
Tel:+86 574 87150672 Fax:+86 574 87157176

E-mail:info@alctron-audio.com www.alctron-audio.com


#### 产品介绍

M588本产品是一款结构紧凑高音质的音频麦克风。麦克风架于热靴装置上能够减少外围环境的干扰,从而更加专注于音频。其心型指向性麦克风在拾音的时候更加自然有针对性。当您在外录音的时候防风棉能够减少来自外界的噪音和您不需要的声音。此款麦克风主要用于单反相机或者摄像机,提供高品质的音质。此麦克风不仅配备一个相机热靴装置同时还配备防震架。

#### 安装

#### 安装到相机:





将话筒壳身插入防震架的安装座 上。确保话筒机身处于中心位子 并且良好平衡。




将话筒热靴座上的固定环逆时针转 动松开;将相机热靴滑入到相机支 架。话筒就位后,顺时针拧紧固定 环。




将3.5mm输出电缆的一端连接到话 筒后部的输出插孔,3.5mm输出电 缆的另一端连接到相机"话筒输 入"插孔。

#### 安装到支杆或话筒支架:




将相机热靴座底部的3/8′′螺纹 连接到您的支杆或者话筒支架所 用的3/8"螺纹。



#### 特征

- \* 体积小巧,造型轻盈; \* 高灵敏度,宽频响;
- \* 实用性强; \* 准确捕捉声音。

### 应用



## 参数

- \* 指向性: 心型
- \* 频响: 10hz-20khz
- \* 最大声压级: 140dB(@1khz, 1% THD into 1kohm load)
- \* 灵敏度: -33dB
- \* 等效噪音级: 20dB

版权所有©宁波奥创电子科技有限公司,所有权保留。必要的技术数据和外观更改恕不予以另行通知。

宁波奥创电子科技有限公司 地址:浙江省宁波市海曙区秀丰工业区三成路76号

地址:浙江省宁波巾海堵区秀丰工业区三成路/6号电话:+8657488009874

传真: 0574-87157176 邮箱: sales@alctron-audio.com

网址: http://www.alctron-audio.com

全国统一服务热线: 4000-160-112